

UT8230-12AR-BT

**ALUMINUM UTILITY TRAILER 7X12 BEAVERTAIL
WITH RAMP & RETAINING RAIL 2999# / 3500# GVWR**



Model UT8230-12AR-BT shown with optional bi-fold ramp.

This 7x12 ft heavy-duty single axle utility trailer is ideal for hauling low ground clearance equipment, with a 2 ft beavertail to reduce tailgate height, and an aluminum load retaining rail to keep your cargo in place. Both the standard straight rear ramp and optional bi-fold ramp fold down flat on the trailer deck when hauling empty. Every Chilton Trailer is built by hand with a fully welded frame and ramp for years of reliability.

STANDARD FEATURES

- 2 ft beavertail (8-degree angle)
- Straight rear load ramp
- 14.5" aluminum load retaining rail
- 5/4" pressure treated lumber deck
- Adjustable swivel jack with wheel
- Spring-loaded ramp locks for easy one-person operation
- Fully welded frame & ramps, reinforced A-frame tongue
- 2999# GVWR (without electric brakes)*

*3500# GVWR with optional 2-wheel electric brakes

OPTIONS

- 2-wheel electric brakes (changes GVWR to 3500#)
- Bi-fold ramp upgrade (adds 4" to total trailer length)
- LED lighting upgrade
- 1100# winch package, 20-ft strap, steel mounting pedestal
- Upgrade to radial tires load range C
- Spare tire pedestal + bracket
- Spare tire ST205/75D-15" load range C
- Radial spare tire upgrade
- Aluminum rims with radial tire upgrade
- Aluminum rim with radial spare tire

SPECIFICATIONS

Trailer Dimensions	102"X218"
Deck Dimensions	82"X144"
Ramp Width	78"
Retaining Rail Height	14.5"
Trailer Weight	830#
GVWR	2999# / #3500
Carrying Capacity	2169#
Carrying Capacity (with brakes)	2670#
Tire Size	15"
Hitch Ball Size	2"



Model UT8230-12AR-BT shown with optional bi-fold ramp.

For warranty information and to register your new trailer, visit www.ChiltonTrailers.com/warranty-registration.