

UT8230-14AR-BT

**ALUMINUM UTILITY TRAILER 7X14 BEAVERTAIL W/  
RAMP & RETAINING RAIL 2999# / 3500# GVW**



Model UT8230-14AR-BT shown with optional bi-fold ramp.

This 7x14 ft heavy-duty single axle utility trailer features a 2 ft beavertail to reduce tailgate height, making hauling low ground clearance equipment easier, with an aluminum load retaining rail to keep your cargo in place. Both the standard straight rear ramp and optional bi-fold ramp fold down flat on the trailer deck when hauling empty. Every Chilton Trailer is built by hand with a fully welded frame and ramp for years of reliability.

**STANDARD FEATURES**

- 2 ft beavertail (8-degree angle)
- Straight rear load ramp
- 14.5" aluminum load retaining rail
- 5/4" pressure treated lumber deck
- Adjustable swivel jack with wheel
- Spring-loaded ramp locks for easy one-person operation
- Fully welded frame & ramps, reinforced A-frame tongue
- 2999# GVWR (without electric brakes)\*
- \*3500# GVWR with optional 2-wheel electric brakes

**OPTIONS**

- 2-wheel electric brakes (changes GVWR to 3500#)
- Bi-fold ramp upgrade (adds 4" to total trailer length)
- LED lighting upgrade
- 1100# winch package, 20-ft strap, steel mounting pedestal
- Upgrade to radial tires load range C
- Spare tire pedestal + bracket
- Spare tire ST205/75D-15" load range C
- Radial spare tire upgrade
- Aluminum rims with radial tire upgrade
- Aluminum rim with radial spare tire

**SPECIFICATIONS**

Trailer Dimensions	102"X218"
Deck Dimensions	82"X168"
Ramp Width	78"
Retaining Rail Height	14.5"
Trailer Weight	960#
GVWR	2999# / #3500
Carrying Capacity	2039#
Carrying Capacity (with brakes)	2540#
Tire Size	15"
Hitch Ball Size	2"



Model UT8230-14AR-BT shown with optional bi-fold ramp.

For warranty information and to register your new trailer, visit [www.ChiltonTrailers.com/warranty-registration](http://www.ChiltonTrailers.com/warranty-registration).