



Model UT8230-14SRAR shown with standard features.

This 7x14 ft heavy-duty single axle trailer hauls everything from an ATV or UTV to a small tractor to landscaping equipment. The side-load ramps are conveniently integrated into the load retaining rail, assembling in seconds. Both the standard straight rear ramp and optional bi-fold ramp fold down flat on the trailer deck for easy hauling when empty. Every Chilton Trailer is built by hand with a fully welded frame and ramps for years of reliability.

STANDARD FEATURES

- Straight rear ramp
- Integrated side load ramps
- 14.5" aluminum load retaining rail
- 5/4" pressure treated lumber deck
- Adjustable swivel jack with wheel
- Spring-loaded ramp locks for easy one-person operation
- Fully welded frame & ramps, reinforced A-frame tongue
- · 2999# GVWR without electric brakes*
- *3500# GVWR with optional 2-wheel electric brakes

OPTIONS

- 2-wheel electric brakes (changes GVWR to 3500#)
- Bi-fold ramp upgrade (adds 4" to total trailer length)
- Premium deck lighting package
- Load lighting
- LED lighting upgrade
- 1100# winch package, 20-ft strap, steel mounting pedestal
- Upgrade to radial tires load range C
- Spare tire pedestal + bracket
- Spare tire ST205/75D-15" load range C
- Radial spare tire upgrade
- · Aluminum rims with radial tire upgrade
- Aluminum rim with radial spare tire

SPECIFICATIONS

Trailer Dimensions	102"X218"
Deck Dimensions	82"X168"
Ramp Width	57"
Retaining Rail Height	N/A
Trailer Weight	1000#
GVWR	2999# / 3500#
Carrying Capacity	1999#
Carrying Capacity (with brakes)	2500#
Tire Size	15"
Hitch Ball Size	2"



Model UT8230-14SRAR shown with standard features.

For warranty information and to register your new trailer, visit www.ChiltonTrailers.com/warranty-registration.