

TT8214-20E

**STEEL TANDEM TRAILER 20FT BEAVERTAIL
WITH RAMP OPTIONS 14000# GVWR**



This 14,000 lb GVWR tandem trailer has an 82"x20ft deck including a 3 ft beavertail, and features heavy duty 6" channel construction with leaf spring axles. Every Chilton Trailer is built by hand with a fully welded frame and ramps for years of reliability.

STANDARD FEATURES

- Full-width split fold up ramp
- Four-wheel electric brakes
- Recessed rubber mounted LED lights
- Rub rail with full size 2x4 stake pockets
- 10,000# spring-loaded trailer jack with pad & fork tubes on both sides
- ST235/80R-16 E radial tires
- 14,000# GVWR

OPTIONS

- Two 17" ramps in lieu of full-width ramp
- Steel load retaining rail, custom height options
- Steel bulkhead rail
- A-frame built-in toolbox
- Spare tire ST205/75D-15 load range C
- Adjustable height coupler
- Pintle, 2-5/16" or collar coupler
- Other beavertail and trailer lengths are available – please contact us to learn more!

SPECIFICATIONS

Trailer Dimensions	102"x303"
Deck Dimensions	82"x241"
Ramp Width	81" or 2x17"
Retaining Rail Height	Multiple options
Trailer Weight	3180#
GVWR	14000#
Carrying Capacity	10820#
Carrying Capacity (with brakes)	10820#
Tire Size	16"
Hitch Ball Size	Multiple options

For warranty information and to register your new trailer, visit www.ChiltonTrailers.com/warranty-registration.