

UT6022-8AR

**ALUMINUM ATV UTILITY TRAILER 5X8 WITH
RETAINING RAIL & RAMP 2200# GVWR**



Model UT6022-8AR shown with optional spare tire, pedestal and bracket.

This 5x8 ft single axle ATV and utility trailer is a compact workhorse, with an aluminum load retaining rail to secure your cargo. Both the standard straight rear ramp and optional bi-fold ramp fold down flat on the trailer deck when hauling empty.

STANDARD FEATURES

- Straight rear load ramp
- 10" aluminum load retaining rail
- Marine-grade 5/8" pressure treated plywood deck
- Adjustable swivel jack with wheel
- Spring-loaded ramp locks for easy one-hand operation
- Fully welded frame & ramp, reinforced A-frame tongue
- 2200# GVWR

OPTIONS

- 5/4 treated wood plank deck in lieu of plywood
- Bi-fold ramp upgrade
- LED lighting upgrade
- 1100# winch package, 20-ft strap, steel mounting pedestal
- Upgrade to radial tires load range D
- Spare tire pedestal + bracket
- Spare tire ST175/80D-13" load range C
- Radial spare tire upgrade
- Aluminum rims with radial tire upgrade
- Aluminum rim with radial spare tire

SPECIFICATIONS

Trailer Dimensions	80"x150"
Deck Dimensions	60"x96"
Ramp Width	57"
Retaining Rail Height	10"
Trailer Weight	400#
GVWR	2200#
Carrying Capacity	1800#
Carrying Capacity (with brakes)	N/A
Tire Size	13"
Hitch Ball Size	2"

For warranty information and to register your new trailer, visit www.ChiltonTrailers.com/warranty-registration.