

UT6030-10AR

**ALUMINUM UTILITY TRAILER 5X10 WITH RAMP
& WOOD SIDES OPTIONS 2999# / 3500# GVWR**



Model UT6030-10AR shown with optional 20" high wood sides.

This 5 x 10 ft single axle heavy-duty utility trailer is compact, yet hauls plenty of gear, from a lumber to landscape equipment. Choose an optional aluminum load retaining rail, or optional 3 wood sides at 11" high or 20" high that are easy to remove. Both the standard straight rear ramp and optional bi-fold ramp fold down flat on the trailer deck for hauling empty. Every Chilton Trailer is built by hand with a fully welded frame and ramp for years of reliability.

STANDARD FEATURES

- Straight rear load ramp
- 5/4" pressure treated lumber deck
- Adjustable swivel jack with wheel
- Spring-loaded ramp locks for easy one-person operation
- Fully welded frame & ramps, reinforced A-frame tongue
- 2999# GVWR (without electric brakes)*
- 3500# GVWR with optional 2-wheel electric brakes

OPTIONS

- 3 wood sides (20" high, 3-board treated lumber) OR
- 3 wood sides (11" high, 2-board treated lumber) OR
- 14.5" high aluminum load retaining rail
- 2-wheel electric brakes (changes GVWR to 3500#)
- Bi-fold ramp upgrade
- LED lighting upgrade
- 1100# winch package, 20-ft strap, steel mounting pedestal
- Upgrade to radial tires load range C
- Spare tire pedestal + bracket
- Spare tire ST205/75D-15" load range C
- Radial spare tire upgrade
- Aluminum rims with radial tire upgrade
- Aluminum rim with radial spare tire

SPECIFICATIONS

Trailer Dimensions	80"x180"
Deck Dimensions	58"x120"
Ramp Width	57"
Retaining Rail Height	14.5"
Trailer Weight	577#
GVWR	2999# / 3500#
Carrying Capacity	2422#
Carrying Capacity (with brakes)	2923#
Tire Size	15"
Hitch Ball Size	2"

For warranty information and to register your new trailer, visit www.ChiltonTrailers.com/warranty-registration.