



This 6×10 ft single axle trailer is light and versatile, with tilt for easy loading. It's available with easily removable wood sides at 20" high or 11" high. Every Chilton Trailer is built by hand with a fully welded frame for years of reliability.

STANDARD FEATURES

- 5/8" marine-grade pressure treated plywood deck
- 2"x4" full size stake pockets
- Fully welded frame
- 2999# GVWR (without electric brakes)*
- *3500# GVWR with optional 2-wheel electric brakes

Model UT7230-10 shown with optional 20" high wood sides.

OPTIONS

- 2-wheel electric brakes (changes GVWR to 3500#)
- 4 wood sides (20" high, 3-board treated lumber) OR
- 4 wood sides (11" high, 2-board treated lumber)
- 5/4" pressure treated deck boards in lieu of plywood
- · Adjustable swivel jack with wheel
- Upgrade to radial tires load range C
- LED lighting upgrade
- 1100# winch package with 20-foot strap
- Spare tire pedestal (aluminum) + bracket
- Spare tire ST205/75D-15" load range C
- Radial spare tire upgrade
- Aluminum rims with radial upgrade
- · Aluminum rim with radial spare

SPECIFICATIONS

Trailer Dimensions	90"x178"
Deck Dimensions	72"x122"
Ramp Width	N/A
Retaining Rail Height	N/A
Trailer Weight	660#
GVWR	2999# / 3500#
Carrying Capacity	2339#
Carrying Capacity (with brakes)	2840#
Tire Size	15"
Hitch Ball Size	2"

For warranty information and to register your new trailer, visit www.ChiltonTrailers.com/warranty-registration.