

UT8250-17BSRAR

ALUMINUM ATV UTILITY TRAILER 7X17 WITH SIDE LOAD RAMPS, BUMPOUT & RAIL 5000# GVWR



Model UT8250-17BSRAR shown with optional bi-fold ramp.

This 7x17 ft heavy-duty tandem trailer hauls your ATV and UTV with room to spare. The front 79" of trailer deck is bumped out to 97" wide to accommodate a side-loaded ATV. Side-load ramps are conveniently integrated into the load retaining rail and assemble in seconds. Both the standard straight rear ramp and optional bi-fold ramp fold down flat on the trailer deck for easy hauling when empty. Every Chilton Trailer is built by hand with a fully welded frame and ramps for years of reliability.

STANDARD FEATURES

- 97" wide bump-out of front 79" of trailer deck
- Integrated side load ramp for ATV
- 14.5" aluminum load retaining rail
- 5/4" pressure treated lumber deck
- Electric brakes
- Adjustable swivel jack with wheel
- Spring loaded ramp locks for easy one-person operation
- Fully welded frame & ramps, reinforced A-frame tongue
- 5000# GVWR (each axle rated for 3500#)

OPTIONS

- Bi-fold ramp upgrade
- Premium deck lighting package
- Load lighting
- LED lighting upgrade
- Adjustable channel for pintle
- 2-5/16" coupler
- 1100# winch package, 20 ft strap, steel mounting pedestal
- Upgrade to radial tires load range C
- Spare tire pedestal + bracket
- Spare tire ST205/75D-15" load range C
- Radial spare tire upgrade
- Aluminum rims with radial tire upgrade
- Aluminum rim with radial spare tire

SPECIFICATIONS

Trailer Dimensions	102"x258"
Deck Dimensions	82"x203" with 79"x97" bumpout
Ramp Width	78"
Retaining Rail Height	14.5"
Trailer Weight	1600#
GVWR	5000#
Carrying Capacity	3400#
Carrying Capacity (with brakes)	3400#
Tire Size	15"
Hitch Ball Size	2"



Model UT8250-17BSRAR shown with optional bi-fold ramp.



For warranty information and to register your new trailer, visit www.ChiltonTrailers.com/warranty-registration.