

## UT8270-16SRAR-BT

### ALUMINUM ATV UTILITY TRAILER BEAVERTAIL 7X16 WITH SIDE LOAD RAMPS & RAIL 7000# GVWR



Model UT8270-16SRAR-BT shown with optional bi-fold ramp.

This 7x16 ft heavy-duty tandem trailer easily hauls your ATV and UTV, with a 2 ft beavertail and side-load ramps conveniently integrated into the load retaining rail. Both the standard straight rear ramp and optional bi-fold ramp fold down flat on the trailer deck for easy hauling when empty. Every Chilton Trailer is built by hand with a fully welded frame and ramps for years of reliability.

#### STANDARD FEATURES

- 2 ft beavertail (8 degree angle)
- Integrated side load ramps for ATV
- 14.5" aluminum load retaining rail
- 5/4" pressure treated lumber deck
- 4 wheel electric brakes
- Adjustable swivel jack with wheel
- 7000# coupler
- Spring loaded ramp locks for easy one-person operation
- Fully welded frame & ramps, reinforced A-frame tongue
- LED lights
- Radial tires, load range D (1 year replacement warranty)
- 7000# GVWR (each axle rated for 3500#)

#### OPTIONS

- Bi-fold ramp upgrade (adds 4" to total trailer length)
- Add aluminum expanded metal cover on ramp (straight or bi-fold)
- Adjustable channel for pintle, 2-5/16" coupler or 2" ball
- 1000# winch package, 20 ft strap, steel mounting pedestal
- Spare tire ST205/75R-15"
- Aluminum rims upgrade
- Aluminum rim with spare tire
- U-bolt attaching bracket for spare tire
- Ramp stands

#### SPECIFICATIONS

Trailer Dimensions	102"x249"
Deck Dimensions	82"x192"
Ramp Width	78"
Retaining Rail Height	11"
Trailer Weight	1400#
GVWR	7000#
Carrying Capacity	5600#
Carrying Capacity (with brakes)	5600#
Tire Size	15"
Hitch Ball Size	2" ball, 2-5/16" coupler, pintle



Model UT8270-16SRAR-BT shown with optional bi-fold ramp.



Model UT8270-16SRAR-BT shown with optional bi-fold ramp and ramp stands.

For warranty information and to register your new trailer, visit [www.ChiltonTrailers.com/warranty-registration](http://www.ChiltonTrailers.com/warranty-registration).

1125